

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

COTTO DEL CAMPAINO

TECHNICAL CHARACTERISTICS

Available Formats:	4x8, 8x8, 8x16, 16x16, 16x24, 6x7 Hexagon		
Style Description:	Cotto	Glaze Application Method:	Inkjet
Visual Characteristics:	Cotto	Number of Faces/Screens:	4x8: 65, 8x8: 35, 8x16: 30, 16x16: 25, 16x24: 30, Hex: 30
Thickness in mm:	10 MM	Number of Punches/Molds:	4x8: 5, 8x8: 3, 8x16: 2, 16x16: 3, 16x24: 2, Hex: 4
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	Pre Customer 15%	Surface Type:	Matte/Textured
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	Cotto Colors V4, (Bianco Antico) V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	ISO 10545-4 S > 1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".