

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

Tinsel

TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	3 rd Fire raised glaze floral	Glaze Application Method:	Inkjet
Thickness in mm:	9mm	Number of Faces/Screens:	1
Application:	Residential - Interior wall wet/dry - Exterior wall wet/dry Commercial - Interior wall dry	Number of Punches/Molds:	1
Rectified or Pressed:	Rectified	Body Type:	Porcelain
Recycled Content: Post or Pre Customer	7%	Surface Type:	Relief/Raised
		Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Chemical Resistance:	EN ISO 10545-13 GA, GLA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	N/A
Frost Resistant:	Yes	Breaking Strength:	1600N
PEI/Abrasion Resistance:	N/A	Thermal Shock Resistance:	Resistant

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.